

3. The evaporator as claimed in claim 1, wherein the wall thickness (e_1) of a tube lies between 0.2 and 0.7 mm.
4. The evaporator as claimed in claim 1, wherein the internal thickness (e_2) of a tube lies between 0.6 and 1.8 mm.
5. The evaporator as claimed in claim 1, wherein the corrugation half-period ($p/2$) of the spacers lies between 1.0 and 1.8 mm.
6. The evaporator as claimed in claim 1, wherein the wall thickness (e_2) of the spacers lies between 0.05 and 0.1 mm.
7. The evaporator (10) as claimed in claim 1, wherein the tubes and the fluid boxes (18, 21) are in the form of a stack of pouches (11) each formed from two sheet-metal plates (12, 13) stamped into the shape of cups, the concavities of which are turned towards one another and which are brazed together so as to be leak tight at their periphery, each pouch defining one of the said tubes and featuring, at each of its ends, an increased thickness so as to define a segment of fluid box.
8. The evaporator (30) as claimed in claim 1, wherein the fluid boxes are independent components (31, 32) featuring apertures (34) through which penetrate the ends of the tubes (1), the latter being brazed so as to be leaktight to the edge of the apertures.

13. The evaporator (30) as claimed in claim 8, wherein at least one fluid box (31) is formed from two elements (33, 37) delimiting an internal volume (45, 46),

A. 1.
Sub
B1
T E C H N I C A L

A. 2.

A. 2.

21

[illegible]

16. The evaporator as claimed in claim 4, in which the number of passes is chosen between 4 and 6.